



THE ULTIMATE HIGH-PERFORMANCE SCOOTER

GO-GO ELITE TRAVELLER® SPORT

The stylish, high-performing Go-Go Elite Traveller® Sport features an innovative design with a full complement of unique standard features. A charger port conveniently located in the tiller, front and rear LED lighting, 9-inch wheels at front and rear, an additional 2-inch deck space and an increased weight capacity of 23 Stone 3 lbs. are just a few features that make the Go-Go Elite Traveller Sport an exceptional scooter choice.



New LED rear light



Larger 9" wheels



Go-Go Elite Traveller® Sport	4-wheel
Weight capacity:	23 Stone 3 lbs. (147 kg)
Maximum speed ¹ :	Up to 4 mph (6.4 km/h)
Ground clearance ² :	3.8 cm (1.5") at motor
Turning radius ² :	128.3 cm (50.5")
Overall length ² :	109.2 cm (43")
Overall width ² :	54 cm (21.25")
Tyre size:	
Front:	7.62 cm x 22.9 cm (3" x 9") solid
Rear:	7.62 cm x 22.9 cm (3" x 9") solid
Suspension:	Suspension seat post (no frame suspension)
Total weight without batteries ⁴ :	44 kg (100 lbs.)
Heaviest piece when disassembled:	20 kg (44 lbs.) (front section)
Drive system:	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual braking system:	Regenerative and electromechanical
Standard seating:	Type: Compact foldable molded plastic Weight: 10 kg (23.5 lbs.) Material: Black vinyl Dimensions: 43 cm (17") overall width 43 cm (17") effective depth
Battery requirements ³ :	Two 12-volt, deep cycle (standard) Size: 2 x 18 AH (standard) Weight ⁵ : 18 AH: 13 kg (29 lbs.) battery pack
Battery charger:	Off-board, 2-amp
Standard colours:	



Blue



Red

2 sets of exciting colours with every scooter!

Features

- Front and rear LED lighting
- Feather-touch disassembly with one hand
- Additional 2 inches of deck space for added leg room
- Exclusive black, low-profile, non-scaffing tyres with new tri-spoke mags
- Delta tiller with wraparound handles
- 22.9 cm (9") wheels
- 23 Stone 3 lbs. (147 kg) weight capacity
- Auto-connecting front to rear cable
- Includes 2 sets of easily changeable coloured panels - Red & Blue
- Front frame-mounted seat post offers maximum stability
- Modular design for easy serviceability
- Microprocessor-based controller offers optimal power management and added safety features
- Front tiller-mounted basket
- Charger port conveniently located in the tiller
- Suspension seat post

Options

- Cup holder
- Rear basket
- Crutch holder

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. This specification can be subject to a variance of + 10%, -5%.

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³ AGM or gel cell type required.

⁴ Includes standard seat.

⁵ Battery weight may vary based on manufacturer.

The information contained herein is correct at the time of publication; due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice.

NOTE: This product conforms to all applicable ANSI/RESNA testing requirements and ISO 7176 series EN12184 standards. All specifications subject to change without notice.

32 Wedgwood Road, Bicester, Oxfordshire OX26 4UL

(Tel) 01869 324 600 • (Fax) 01869 323 070 • www.pridemobility.co.uk

